



友利貿易私人有限公司
UNITRA JAYA TRADING PTE. LTD.

Business Registration No.03327/1987W
GST REG. NO. M2-0078342-5

BLOCK 1076, EUNOS AVE. 6, #01-157 SINGAPORE 409632
TEL: 6748 2388 (3 LINES), 6747 5000, 6745 8820 FAX: (65) 6745 7133
Email: unitra@singnet.com.sg.

ZENYA NS-300 HOT AIR WELDER FOR THERMOPLASTICS



- **HIGH PERFORMANCE DESIGN**
- **NON-LUBRICATING ROTARY BLOWER**
- **COMPACT AND EASY-TO-CARRY**
- **LIGHT-WEIGHT AND EASY-TO- HOLD WELDING GUN**
- **HIGH TEMPERATURE PARTS UTILIZE STAINLESS STEEL WEBBING**
- **HIGH DURABILITY**

Features

1. The lack of lubricating oil to change means less hassle and no oil in the hot air from the welding gun.
2. Easy-to-carry as the motor, rotary blower, transformer and switch board have all been incorporated into a small frame body.
3. Utilizes a condenser motor. The absence of a starter switch means less down-time and longer machine life.
4. The welding gun is light-weight and all parts which reach a high temperature incorporate stainless steel webbing, enabling the unit to withstand usage over a prolonged period.
5. The air cock is completely insulated from the body pipe by the gun grip so there is no chance of an electric shock.
6. Replacement of the heating bobbin is simple and easy.
7. Can be used continuously over an extended period of time
8. Longer lasting than most brands with average motor life of more than 3 years*

Main Applications

1. All types of container production associated with plastics factories and processors (ex. manufacturing of square tanks, etc.)
2. Pipe laying work, duct lining, conduit fitting and water pipe work
3. Construction of vinyl chloride gutters and processing of construction materials
4. Welding of extrusion-molded plastics
5. Welding and repair of vehicles and boats
6. Interior work on vehicles, boats and shops
7. Plastic displays, construction of sign boards

*motor life expectancy varies with user

Specifications	
Voltage	220 V~230 V
Power Source	50/60Hz
Dimensions of steel ease - W X L X H	310 X 200 X 220 mm
Power	260 W
Dimensions - W X L X H	275 X 138 X 196 mm
Weight	9.8 kg
Electric motor	Single-phase condenser motor, bipolar, 3,000~3,600r.p.m.
Air pressure	0.3kgf/cm ² (0.029MPa) 50 /min
Max. air temp.	300°C (10mm from the nozzle tip)
Temp, adjustment	Output voltage to gun adjustable in 7 steps (40-100V)
Blower features	Oil-less type, utilises 4 special RG heat-resistant lubricated vanes

Accessories Include

- Rotary blower with switchboard x 1
- FL gun x 1
- Air hose x 1
- Spare heating bobbin x 1
- 4mm nozzle x 1
- steel storage case x 1

Warranty

- Six-months carry in warranty for machine only